



American National Standard for

Rotodynamic Vertical Pumps of Radial, Mixed, and Axial Flow Types

for Design and Application

ANSI/HI 2.3-2013



6 Campus Drive
First Floor North
Parsippany, New Jersey
07054-4406
www.Pumps.org

This page intentionally blank.

ANSI/HI 2.3-2013

American National Standard for

Rotodynamic Vertical Pumps of Radial, Mixed, and Axial Flow Types

for Design and Application

Sponsor
Hydraulic Institute
www.Pumps.org

Approved December 19, 2013
American National Standards Institute, Inc.

American National Standard

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgement of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Buyers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published By

Hydraulic Institute
6 Campus Drive, First Floor North
Parsippany, NJ 07054-4406

www.Pumps.org

Copyright © 2013 Hydraulic Institute
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN 978-1-935762-17-1



Recycled
paper

Contents

	Page
Foreword	vii
2.3 Design and application	1
2.3.1 Scope	1
2.3.1.1 Preferred units for pump applications	1
2.3.1.2 Specific speed and suction specific speed	1
2.3.1.3 Introduction to pump classifications	5
2.3.2 Impeller types	5
2.3.3 Mechanical features	7
2.3.3.1 Radial thrust	7
2.3.3.2 Axial thrust	8
2.3.3.3 Shafting	14
2.3.3.4 Open line shaft and enclosed line shaft	16
2.3.3.5 Types of bearing bushings and spacing	16
2.3.3.6 Lubrication systems	19
2.3.3.7 Shaft seals	20
2.3.3.8 Nozzle loading	26
2.3.3.9 System piping and foundation	26
2.3.3.10 Structural natural frequencies	26
2.3.3.11 Motor/Driver interface	27
2.3.4 Pump performance, selection criteria	30
2.3.4.1 Pumping system requirements	30
2.3.4.2 Pump versus system curves	31
2.3.4.3 System pressure limitation	31
2.3.4.4 Reverse runaway speed	32
2.3.4.5 Water (hydraulic) hammer analysis	32
2.3.4.6 Start-up and shut-down analysis	32
2.3.4.7 Pump and motor speed torque curves	33
2.3.4.8 Predicting pump performance after speed of rotation or impeller diameter change	37
2.3.4.9 Determining operating range, series and parallel operation	39
2.3.4.10 Range of operation	39
2.3.4.11 Continuous, intermittent, and cyclic service	39
2.3.4.12 Operation away from BEP flow	41
2.3.4.13 Intake design and submergence	42
2.3.4.14 Suction piping and cans	42
2.3.4.15 Net positive suction head available (NPSHA)	43
2.3.4.16 NPSHA corrections for temperature and elevation	45
2.3.4.17 NPSH margin considerations	46
2.3.4.18 NPSH requirements for pumps handling hydrocarbon liquids and water at elevated temperatures	47
2.3.4.19 Effects of handling viscous liquids	50
2.3.4.20 Losses	50
2.3.5 Sound levels (dBA)	51
Appendix A Pump classification and general application information	52
A.1 Introduction to pump classifications	52
A.2 Two-phase flow: Liquids with gas	52
A.3 Effect of gas on performance	52
A.4 Vertical pumps used as hydraulic turbines	55
A.5 Rotative speed considerations	57

Appendix B	Other configurations	62
B.1	Introduction to Appendix B	62
B.2	Sump pumps - introduction	62
Appendix C	Materials	78
C.1	Corrosion and erosion in vertical turbine pumps	78
C.2	Protective coatings	80
C.3	Materials for rotodynamic vertical pumps	80
Appendix D	Motors/Drivers	81
D.1	Introduction	81
D.2	Driver types	81
D.3	Electric motors	83
D.4	Variable-speed drives	94
D.5	Gears	94
D.6	Deceleration devices	94
Appendix E	Bibliography	96
Appendix F	Index	98
Figures		
2.3.1a	— Included rotodynamic vertical pump types	2
2.3.1b	— Rotodynamic vertical pump types included in Appendix B	3
2.3.2a	— Enclosed impeller	6
2.3.2b	— Semi-open impeller	6
2.3.2c	— Axial flow impeller (propeller)	6
2.3.2d	— Double suction impeller	6
2.3.2e	— Inducer	7
2.3.3.2.3a	— Enclosed impeller plain top shroud	9
2.3.3.2.3b	— Semi-open impeller	9
2.3.3.2.3c	— Enclosed impeller with back ring and balance holes	9
2.3.3.2.3.1a	— Enclosed end of shaft at suction	10
2.3.3.2.3.1b	— Shaft sleeve through packing or mechanical seal	11
2.3.3.2.3.1c	— Shaft sleeve through pressure breakdown bushing	11
2.3.3.2.5	— Experimental thrust coefficient C	12
2.3.3.2.7	— Axial thrust versus rate of flow curves	15
2.3.3.4a	— Open line-shaft, product-lubricated, vertical turbine pump	17
2.3.3.4b	— Enclosed line-shaft, oil-lubricated, vertical turbine pump	17
2.3.3.4c	— Open line shaft	18
2.3.3.4d	— Enclosed line shaft	18
2.3.3.7.1a	— Mechanical seal classification by arrangement	20
2.3.3.7.1b	— Mechanical seal classification by design	21
2.3.3.7.3a	— External seal	22
2.3.3.7.3b	— Internal seal arrangement	23
2.3.3.7.3c	— Special seal arrangement	24
2.3.3.7.4a	— Stuffing box for low to intermediate pressure service	25

2.3.3.7.4b — Stuffing box with injection	25
2.3.3.11.4a — Solid-shaft motor	28
2.3.3.11.4b — Hollow-shaft motor	28
2.3.3.11.4.2 — Head shaft coupling, rigid style	29
2.3.3.11.5a — Flanged adjustable coupling, rigid style	30
2.3.3.11.5b — Flanged adjustable spacer coupling, rigid style	30
2.3.4.2 — Pump performance versus system curve	31
2.3.4.7a — Torque versus speed - metric units	35
2.3.4.7b — Torque versus speed - US customary units	36
2.3.4.8 — Impeller with angled outside diameter	38
2.3.4.9a — Series operation	39
2.3.4.9b — Parallel operation	40
2.3.4.10 — Operating range	40
2.3.4.14 — Suction cans (barrels) with vents	43
2.3.4.18a — NPSHR reduction for pumps handling hydrocarbon liquids and high-temperature water (metric units)	48
2.3.4.18b — NPSHR reduction for pumps handling hydrocarbon liquids and high-temperature water (US customary units)	49
A.1 — Overhung pump types and classifications	53
A.2 — Between-bearings pump types and classifications	54
A.3 — Vertically suspended pump types and classifications	54
A.4 — Effect of gas on pump performance	55
A.5 — Turbine characteristics for pumps with $n_s < 50$ (2500)	56
A.6 — Turbine performance	57
A.7 — Recommended maximum operating speeds for single suction pumps (metric units)	59
A.8 — Recommended maximum operating speeds for single suction pumps (US customary units)	60
B.1 — Type VS4 line-shaft design sump pump	63
B.2 — Rate of flow versus minimum submergence	67
B.3 — Tailpipe and float control	68
B.4 — Schematic showing vaporproof/pressurized design	70
B.5 — Alarms and controls	71
B.6 — Applied forces and moments	71
B.7 — Type VS5 cantilever shaft design sump pump	72
B.8 — Rate of flow versus minimum submergence	75
B.9 — Applied forces and moments	77
D.1 — Typical torque–speed curves for NEMA design AC motors	88
D.2 — Torque–speed curves for design A, B, C, and D for AC motor	89
Tables	
2.3.1.2 — Principal symbols	4
D.1 — Drivers – functions and parameters for selection	81
D.2 — Common electric motor enclosure types	85

D.3 — Definition of first numeral in IP classification system	86
D.4 — Definition of second numeral in IP classification system	86

Foreword (Not part of Standard)

Scope

The purpose and aims of the Institute are to promote the continued growth of pump knowledge for the interest of pump users and pump manufacturers and to further the interests of the public in such matters as are involved in manufacturing, engineering, distribution, safety, transportation, and other problems of the industry, and to this end, among other things:

- a) To develop and publish standards for pumps;
- b) To collect and disseminate information of value to its members and to the public;
- c) To appear for its members before governmental departments and agencies and other bodies in regard to matters affecting the industry;
- d) To increase the amount and to improve the quality of pump service to the public;
- e) To support educational and research activities;
- f) To promote the business interests of its members but not to engage in business of the kind ordinarily carried on for profit or to perform particular services for its members or individual persons as distinguished from activities to improve the business conditions and lawful interests of all of its members.

Purpose of Standards

- 1) Hydraulic Institute Standards are adopted in the public interest and are designed to help eliminate misunderstandings between the manufacturer, the purchaser, and/or the user and to assist the purchaser in selecting and obtaining the proper product for a particular need.
- 2) Use of Hydraulic Institute Standards is completely voluntary. Existence of Hydraulic Institute Standards does not in any respect preclude a member from manufacturing or selling products not conforming to the Standards.

Definition of a Standard of the Hydraulic Institute

Quoting from Article XV, Standards, of the By-Laws of the Institute, Section B:

"An Institute Standard defines the product, material, process or procedure with reference to one or more of the following: nomenclature, composition, construction, dimensions, tolerances, safety, operating characteristics, performance, quality, rating, testing and service for which designed."

Comments from users

Comments from users of this standard will be appreciated, to help the Hydraulic Institute prepare even more useful future editions. Questions arising from the content of this standard may be directed to the Technical Director of the Hydraulic Institute. The inquiry will then be directed to the appropriate technical committee for provision of a suitable answer.

If a dispute arises regarding contents of an Institute publication or an answer provided by the Institute to a question such as indicated above, then the point in question shall be sent in writing to the Technical Director of the Hydraulic Institute, who shall initiate the Appeals Process.

Revisions

The Standards of the Hydraulic Institute are subject to constant review, and revisions are undertaken whenever it is found necessary because of new developments and progress in the art. If no revisions are made for five years, the standards are reaffirmed in accordance with the *ANSI Essential Requirements*.